



Zeron

Series



Surface Mounted Measurements (mm)	Fixed One Measurements (mm)	Fixed Two Measurements (mm)
Absolute Luminous Flux 20W (500mA) 1743lm (at 3000K)	Absolute Luminous Flux 20W (500mA) 1743lm (at 3000K)	Absolute Luminous Flux 24W (500mA) 1732lm (at 3000K)
Beam 40° (M)	Beam 40° (M)	Beam 40° (M)
Mini Surface Mounted Measurements (mm)	Mini Fixed One Measurements (mm)	Mini Fixed Two Measurements (mm)
Absolute Luminous Flux 7W (700mA) 545lm (at 3000K)	Absolute Luminous Flux 7W (700mA) 545lm (at 3000K)	Absolute Luminous Flux 12W (500mA) 1000lm (at 3000K)
Beam 30° (M)	Beam 30° (M)	Beam 30° (M)

Product Collection	Beam Options
 Athena Series Page 194	 Medium (Surface Mounted) 30°, 40° (M)
	 Medium (Fixed One) 30°, 40° (M)
	 Medium (Fixed Two) 30°, 40° (M)

Finishes		LED	
UV Textured Black		Colour Temp	3000K, 4000K
UV Textured White		CRI (Ra/R9)	80+ / >0
UV Textured Grey ¹		Efficacy	Up to 81lm/W
General Specifications		Colour Deviation	
Material	Powder Coated Aluminium	Standard	SDCM≤2
IP	65	Mini	SDCM≤3
Warranty		Lifetime	
Standard	5 Years	Standard	>55,000h L80B10
Mini	3 Years	Mini	>60,000h L80B10
		Driver	
		240V Built-in Phase-Cut Dimmable Driver	
		240V Remote Tridonic one4all / Osram DALI Driver (TD/OD)	
		240V Remote Tridonic basicDIM Bluetooth Driver (TB)	



Notes
¹Textured Grey only available for Zeron Mini 3000K.